

Features:

- AP15-TUC:**
- 15W High Efficiency Compression Driver
 - 25 or 70VRMS field selectable
 - Vandal-Resistant, Weatherproof Construction
 - Recommended for High Intelligibility Paging, Intercommunication, and Signaling

- Amplified Speakers:**
- 24VDC polarized operation (120VAC on some models)
 - Die cast aluminum circuitry housing
 - Indoor or outdoor mounting.
 - NEMA 3 rated enclosure

Description:

The Industrial Series includes:
 15W Fire Rated Loudspeaker
 Amplified Speakers, Hazardous Area Amplified Speakers and Explosion Proof Speakers.

The UL listed 15W Fire Rated Horns are equipped with a compression driver providing up to 15 watts RMS power handling capability, and weather resistant metal construction.

The ASHP, ASHH, ASHX series speakers provide additional power to a system without having to add more amplifiers.


All are designed for surface mounting.

Ordering Information:


<u>Model Number</u>	<u>Description</u>
AP-15TUC	Fire Rated Horn speaker., grey - <i>std color</i> , red - <i>opt.</i> 25/70V 1/2, 1, 2, 4, 7-1/2, 15W taps.
ASHP-24SMR-25	24VDC. 25VRMS Speaker Amplifier
ASHP-24SMR-70	24VDC, 70VRMS Speaker Amplifier
ASHP-ACSMR-25	120VAC, 25VRMS Speaker Amplifier
ASHP-ACSMR-70	120VAC, 70VRMS Speaker Amplifier
ASHH-24SMR-25	Division 2 Hazardous Area Speaker Amplifier 24VDC, 25VRMS
ASHH-24SMR-70	Speaker Amplifier 24VDC, 70VRMS
ASHX-24SMR-25	Explosion Proof (Class I, Div. 1, Groups B, C, & D) Speaker Amplifier 24VDC, 25VRMS
ASHX-24SMR-70	Speaker Amplifier 24VDC, 70VRMS




Industrial Speakers



AP15-TUC



Amplified Speaker



Hazardous Area
Amplified Speaker



Explosion Proof
Amplified Speaker

Listings:



S5661



6911-1446:100

Specifications:



Model Number	Power Rating	Frequency Response	Sound Output UL 3dB increment	Anechoic
AP-15TUC	15 Watts continuous	400 - 4,000 Hz	102db@10' 15W	120db@1meter 15W (peak)

Model Number	Input Voltage	Standby Current	Wattage Draw @ 25Vrms)	UL dB(A) Sound Pressure	dB(A) Sound Power
ASHP Series	24VDC	.060A	.015W	97	118.7
ASHH Series	24VDC	.060A	.015W	97	118.7
ASHX Series	24VDC	.060A	.015W	97	118.7

Specifications are subject to change without notice. Specifications are provided for information only and no responsibility is assumed by Evax Systems, Inc. For their use.